

Product Data Sheet

Code Number : RH60-RB

NO	Item	Specification	Standard
1	Appearance	Bright and shiny surface finishes	
2	Alloy	Sn60/Pb40	JIS-Z-3282 A CLASS
3	Melting Point	190°C	DSC
4	Flux Content	2.0±1 %	JIS-Z-3283
5	Halide Content	0.5~1.0%	JIS-Z-3283
6	Spread ability	> 80%	JIS-Z-3197
7	Gravity	8.5	
8	Packaging	200g, 250g, 500g, 1kg/Rool	JIS-Z-3283
9	Diameters Tolerances	0.3~0.6± 0.05 mm , 0.8~1.6 ± 0.1 mm	JIS-Z-3283
10	Flux Type	ROL1	J-STD-004
11	Features	Excellent solder joint reliability. Superior joint strength. Excellent thermal & Mechanical fatigue resistance. Low cleaning required after solder joint	
12	Purpose	For use in applications requiring good activation.	

Physical Properties & Reliability Data

No	Test Item	Test Result	Test Method
1	Silver Chromate Test	PASS	IPC-TM-650, 2.6.33
2	Copper Mirror Test	PASS	IPC-TM-650, 2.6.32
3	Copper plate Corrosion	PASS	JIS-Z-3197, 6.6.1
4	S.I.R Test	1×10 ⁹ up	IPC-TM-650, 2.6.3.3
5	Electro migration Test	1×10 ⁹ ¹² up	IPC-TM-650, 2.6.14.1

ALLOY COMPOSITION

(Sn)	(Pb)	(Sb)	(Cu)	(Bi)	(Zn)	(Fe)	(Al)	(As)	(Cd)
59~61	REM	0.12 MAX	0.05 MAX	0.10 MAX	0.002 MAX	0.02 MAX	0.002 MAX	0.03 MAX	0.002 MAX